

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants – Greases

Copper Compound

Heavy Duty anti-seize assembly product and lubricant that can be used over a wide temperature range from -30°C. to +1200°C.

The product can be used on screw threads and other mating surfaces to prevent seizure from rust and corrosion or from high temperatures. It may be applied up to 12 months prior to requirement.

Performance levels

Copper Compound
Suitable for all screw threads and other mating surfaces

Applications

Suitable for many applications like; screw threads, bolts & nuts, piping assemblies, spark plugs, wheel nuts, disc pads, battery terminals, off-shore equipment, turn tables, bridge bearings, etc.

Suitable for diverse equipment like; Automotive equipment, hinges, sliding surfaces, chains & cables etc.

Agricultural and forestry machines.

Industrial applications in factories and workshops.

Steel ropes and cables of machinery and lifts.

Features and Benefits

Superior performance

Copper Compound ensures excellent lubrication and protection, even under high pressure and high temperatures circumstances and with slow and interrupted machinery movement.

Superior protection

The product protects against rust and corrosion. Guards against fretting and scuffing.

Multi purpose applications

Copper Compound is suitable as an anti-seize compound and lubricant for all screw threads and Other mating surfaces.

Severe working conditions

Copper Compound can handle temperatures from -30°C. to +1200°C.

High pressures and high temperatures are no problem for this product.

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil or grease to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Copper Compound	
Appearance	Thick grease
Texture	smooth
Colour	Copper yellow
Application temperature °C.	-30 - +1200
Shelflife	2 years
Storage	Cool & dry

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:
AdG

This information only applies to products manufactured in the following location(s): Europe

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2011, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.