

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants - Engine Oil - Heavy Duty Engine Oils

Version: 106/05c

Valvoline™ HD Engine Oil SAE 30

Quality single grade formulation for heavy-duty applications

Valvoline HD Engine Oil SAE 30 is a premium quality, heavy-duty motor oil, for use in gasoline and diesel engines where the engine manufacturer recommends a single grade motor oil.

Approvals/Performance levels

SAE 30
API CF-4, SG
Caterpillar TO-2
MAN 270

Applications

Suitable for heavy-duty engines where single grade motor oils are recommended.

Specially engineered for use in service fleets where it helps prevent formation of sludge caused by frequent stop-and-go driving.

Can also be used, in some cases, as hydraulic oil or gear oil where specified by the manufacturer of the machine.

Suitable for older Caterpillar TO-2 transmissions and industrial gearboxes with the ISO 68 standard.

Can be used as hydraulic oil with the ISO 100 qualification.

Features and Benefits

Wear protection

Strong oil film protects the engine against wear and corrosion.

Engine cleanliness

Helps prevent formation of sludge caused by frequent stop-and-go driving.

Breakdown resistance

Thermal and Oxidation stable oil film.

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

SAE Viscosity Grade	30
Viscosity, mm²/s @ 100 °C. ASTM D-445	10.5
Viscosity, mm²/s @ 40 °C. ASTM D-445	85.1
Viscosity Index ASTM D-2270	106
TBN, mg KOH/g ASTM D-2896	6.4
Pour Point, °C ASTM D-5950	-24
Specific Gravity @ 15.6°C. ASTM D-4052	0.885
Flash Point, COC, °C. ASTM D-92	232

This information only applies to products manufactured in the following location(s): Europe

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 106/04

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2011, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.