



GEAR MB 80W

Gearbox lubricant

Extreme Pressure

TYPE OF USE

Specially designed for truck gearboxes : Mercedes Benz, MAN or ZF (Ecolite, Ecomid, Ecosplit, Astronic 1&2 without Intrader).

All gearboxes and gearbox/differential without limited slip system operating under moderate loads and revolution speed or transfer gearboxes, mechanical transmissions without hypoid gear, reduction gears operating under moderate to severe load and revolution speed.

PERFORMANCES

STANDARD : API GL-4

APPROVALS : Mercedes BENZ page 235.1, MAN 341N, ZF TE-ML 02A / 17A

Extreme pressure lubricant for an efficient anti wear protection.

Very high lubricating properties to reduce friction.

Suitable for any type of seal

Anti-corrosion, Anti-foam.

RECOMMENDATION

Oil change : According to manufacturer's requirements and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE J306	80W
Density at 15°C (59°F)	ISO 12185	0.886
Viscosity at 40°C (104°F)	ASTM D445	89.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.8 mm ² /s
Viscosity Index	ASTM D2270	105
Flash Point	ASTM D92	219°C / 426°F
Pour Point	ASTM D97	-30°C / -22°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 . Site Web : www.motul.fr

8075

02/03