



PowerJet 4T 10W-40

4 Stroke engine oil for Jet Ski

Technosynthese

TYPE OF USE

Specially designed for jet ski 4 stroke engines, turbocharged or supercharged. Leisure or racing use.
Suitable for catalytic converters.
Suitable for leaded or unleaded gasoline.

PERFORMANCES

STANDARDS **API SJ**

The reinforced synthetic base stock provides very high lubricating power which reduces frictions for higher power output and ensures resistance to very high temperatures reached in modern engines. Outstanding detergent/dispersent power avoiding sludge and deposits in the crankcase and maintaining engine cleanliness.

Protects against salt fog corrosion.
Anti-oxidation, Anti-wear, Anti-foam properties.

RECOMMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.870
Viscosity at 100°C (212°F)	ASTM D445	14.7 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	94.0 mm ² /s
Viscosity index	ASTM D2270	164
Pour point	ASTM D97	-36°C / -33°F
Flash point	ASTM D92	231°C / 447°F
TBN	ASTM D2896	8.0 mg KOH/g