

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants – Transmission Oils- Automotive.

Version: 234/01a

MaxLife™ MTF GL-4 SAE 75W-80

Multi-vehicle gear oil.

Mild EP gear oil suitable for gearboxes and transaxles when the manufacturer specifies a GL-4 SAE 75W-80 oil.

MaxLife MTF GL-4 SAE 75W-80 provides outstanding protection and lubrication of the gearbox over a wide temperature range.

Performance levels

SAE 75W-80
API GL-4
Alfa Romeo
BMW
Citroën
Dacia
Fiat
Mini
Mercedes-Benz
Honda
Peugeot
Renault
Seat
Skoda
Smart
VW
Volvo

*check owners manual before use

Applications

Suitable for handshifted gearboxes and transaxles of passenger cars, vans, trucks, and buses where the manufacturer recommends a GL-4 transmission oil with a viscosity of SAE 75W-80.

This product can be used in many models of the mentioned vehicle brands and more, but always check first the *Owners Manual* or the *Valvoline Oil Advisor* on www.valvolineurope.com

Features and Benefits

Superior protection

Optimum protection against wear and tear, also under high stress working conditions. Modern additives protect against corrosion, oxidation, foam, and deposits.

Breakdown resistance

Modern base oils and a highly balanced additive system avoid breakdown situations.

Consistent viscosity

Good viscosity-temperature properties
Highly stable viscosity even at low temperatures.

Fuel Economy properties

By smooth lubrication, the product has light fuel economy properties.
Easy oil circulation gives better cooling and with that also light fuel savings.

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

MaxLife MTF GL-4	
SAE Viscosity Grade	75W-80
Viscosity, mm ² /s @ 100 °C. ASTM D-445	9.2
Viscosity, mm ² /s @ 100 °C. After shearing(CEC: L-45-T-93).	Stay-in-grade
Viscosity, mm ² /s @ 40 °C. ASTM D-445	51.3
Viscosity Index ASTM D-2270	161
Viscosity, mPa.s -40°C. ASTM D-5293	<150,000
Pour Point, °C ASTM D-5950	-36
Specific Gravity @ 15.6°C. ASTM D-4052	0.879
Flash Point, PMCC, °C. ASTM D-93	190

**This information only applies to products manufactured in the following location(s):
Europe**

People Who Know Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces –

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2012, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.