

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Valvoline™ Ultramax HLP

401/05

Valvoline Ultramax HLP is a premium mineral hydraulic oil specially formulated to meet the stringent requirements of industrial service. This product can be used in all kinds of hydraulic systems, like cranes, forklifts, loading ramps, tail-boards etc. Valvoline Ultramax HLP can be used over a wide range of temperatures. Valvoline Ultramax HVLP is recommended for extremely low temperatures.

Performance levels	Viscosity Grade				
DIN 51524(part 2)	32	46	68	100	150
Sperry Vickers M-2950-S/I-286-S	32	46	68	100	150
US Steel 127	32	46	68	100	150
Thysen-TH N-256132	32	46	68	100	150

Typical Properties	32	46	68	100	150
Viscosity, mm ² /s @ 100 °C	5.5	7.0	8.7	11.0	14.5
Viscosity, mm ² /s @ 40 °C	32	46	68	100	150
Viscosity Index	118	112	105	98	95
TAN; mg KOH/g (ASTM D-664)	1.0	1.0	1.0	1.0	1.0
Pour Point, °C	-39	-30	-27	-18	-15
Specific Gravity @ 15/15°C	0.857	0.876	0.882	0.890	0.895
Flash Point, COC, °C	226	236	245	236	246

This information only applies to products manufactured in the following location(s): Europe

Effective Date: 22-3-2010 Replaces: 402/04 Author's Initials: AdG Code

*Trademark owned by a third party® Registered trademark, Ashland or its subsidiaries © 2010, Ashland

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.

ASHLAND