

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline SynPower ATF

213/04

Valvoline SynPower ATF is a high performance fully synthetic automatic transmission fluid exceeding many leading OEM specifications. Specially formulated for long drain interval requirements, and ideal for all automatic and powershift transmissions; it is also suitable for industrial and hydraulic systems. Valvoline SynPower ATF distinguishes itself by excellent low friction properties, outstanding high- and low temperature fluidity, and high thermal stability. Recommended for use where GM Dexron IIE, Ford Mercon, and others are specified.

Approvals/Performance levels	Viscosity Grade
GM Dexron IIE	
Ford Mercon	
MercedesBenz approval 236.8	
MAN 339 Z-2, 339 V-2	
Allison C-4	
Caterpillar TO-2	
Voith H55.633633 (extended drain) (former Voith G 1363).	
ZF TE-ML 09X, 11A, 14B, 16L.	

Typical Properties	
Viscosity, mm ² /s @ 100 °C	7.0
Viscosity, mm ² /s @ 40 °C	31
Viscosity Index	201
Sulphated Ash, wt. %	0.35
TAN; mg KOH/g (ASTM D-664)	0.9
TBN; mg KOH/g (ASTM D-2896)	3.2
Pour Point, °C	-51
Color, ASTM D-1500	red
Specific Gravity @ 15/15°C	0.835
Flash Point, COC, °C	210

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
Dec. 1, 2008	213/03	AdG	93A

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.