

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants - Engine Oil - Passenger Car Motor Oils

Version: 019/04

SynPower™ FE Motor Oil SAE 0W-30

Premium fully synthetic passenger car motor oil - Provides superior protection, outstanding performance, durability and fuel economy benefits

SynPower FE SAE 0W-30 is recommended for all applications where a Global product SAE 0W-30 is recommended with fuel economy properties. Especially recommended for Volvo* cars.

Approvals/Performance levels

SAE 0W-30
API SL/SJ/CF
ACEA A1/B1-10
ACEA A5/B5-10
Volvo recommended

Applications

Provides the ultimate performance in meeting the latest requirements for virtually all cars and light trucks and vans, including petrol, diesel, and LPG engines, where a 0W-30 is recommended.

For vehicles operating in cold conditions.

Very high quality motor oil, recommended for Volvo passenger cars.

Features and Benefits

Superior protection

Through use of synthetic base oil technology SynPower FE fights the three major causes of engine stress – heat, deposits and wear.

Fuel efficiency

SynPower FE provides outstanding fuel economy benefits.

Deposit control

Reduces formation of sludge and varnish deposits.

Consistent viscosity

Higher tolerance for temperature extremes means oil maintains more consistent viscosity.

Wear protection

Resistant against wear due to oil's extreme pressure properties.

Cold starts

Oil flows easily at very low temperatures.

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

SynPower FE motor oil	
SAE Viscosity Grade	0W-30
Viscosity, mm ² /s @ 100 °C. ASTM D-445	9.4
Viscosity, mm ² /s @ 40 °C. ASTM D-445	47.7
Viscosity Index ASTM D-2270	183
Viscosity, mPa.s -35°C. ASTM D-5293	5300
TBN, mg KOH/g ASTM D-2896	10
Pour Point, °C ASTM D-5950	-48
Specific Gravity @ 15.6°C. ASTM D-4052	0.847
Flash Point, COC, °C. ASTM D-92	226

This information only applies to products manufactured in the following location(s): Europe

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 019/03

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2011, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.