



4000 Motion 15W-50

Gasoline and Diesel Engine Oil

API SL / CF Certified

TYPE OF USE

Specially designed for recent cars, powered by Diesel, Turbo Diesel or Gasoline engines with injection and catalytic converter.

Suitable for all types of Gasoline or Diesel engines, using all types of leaded or unleaded fuel, Diesel fuel, and LPG.

PERFORMANCE

STANDARDS ACEA A3 / B3 - API **SL** / CF
APPROVALS MB-Approval 229.1

** The new API **SL** standard is more stringent than API **SJ** in terms of aging resistance (average drain interval increased), requires anti-oxidation properties to maintain a constant viscosity avoiding sludge and deposits in the crankcase, anti-wear properties and dispersant power.*

Detergent, dispersive agents and anti-oxidation additivation are particularly reinforced to ensure longer drain intervals, required by manufacturers for their new car models.

Very efficient anti-deposit and anti-black sludge power which maintains a clean engine.

Outstanding protection at high temperature.

Anti-corrosion, anti-foam properties.

RECOMMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.

MOTUL 4000 Motion 15W-50 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-50
Density at 20°C (68°F)	ASTM D1298	0.881
Density at 100°C (212°F)	ASTM D445	19.5 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	147.4 mm ² /s
Viscosity index	ASTM D2270	151
Pour point	ASTM D97	-27°C / -16.6 °F
Flash point	ASTM D92	204°C / 399.2°F
TBN	ASTM D2896	8.0 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE.

MOTUL, 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site : www.motul.fr

01/10